

BELCO SHOOTING-FRACCRING REPORT

E.L.L.	22A-21-565-40-406 OFFICIAL NUMBER	LD6-16 BELCO NUMBER	LOBITOS OFFSHORE AREA	APR NR
SEA WATER ACCING FLUID	Rio BRAVO FORMATION	6360'-5840' INTERVAL	402 MNF, 321 VNF NET SAND	99520 TOTAL VOL. TREAT. (g/m)

OPERATIONAL RESULTS

Interval	1 st	2 nd	3 rd							
Interval: From:	6370	5820	5420							
(ft) To:	5834	5546	4980							
NET SAND: MNF	104	153	145							
VNF	82	123	116							
DATE:	25/04	26/04	26/04							
SHOOTING Started at:	18:45'	21:30	6:00							
Finished at:	19:30'	04:30	8:30							
Shots	30	33	42							
DATE:	25/04/84	26/04/84	26/04/84							
ACCING Started at:	20:30'	4:50'	8:55'							
Finished at:	20:50'	5:50'	9:35'							
Break down	2800	2800	2800							
Pressure										
(psi)										
St. shut-in press. (psi)										
Rate	25.5	27	26.5							
(PM)										
Average										
Maximum	3200	3400	3400							
Pressure Minimum	2800	2800	2500							
(psi) Average	3000	3100	2950							
Standing	2000	2200	2600							
Final (10')	1800	2080	2040							
Volume of Treatment (g/m)	17270	41070	40580							
Capillary loss:	/	/	/							
Loss g/m:										
Loss g/m:	11820	35360	35470							
Loss g/m:	300	600	600							
Displacement loss:	5960	5710	5080							

MATERIALS

SAND	20/40	66	198	191	465					
(Sxs)	10/20	72	202	263	537					
Support carry (lb/gal)										
nc. Form (3M/VNF)										
FRAC/FRD (Gms)	18	40	41	99						
CLASTA (Gms)	17	42	40	99						
GBW-3 (H61)	10	21	21	52						
KEL (Sxs)	24	22	23	69						
WG-11 (Sxs)	19	17	24	60						
EN ball sealers	—	24	24							

DATE: 30/04/84 DISTRIBUTION: DALL & WALKER