



Weatherford

SONIC LOG
MSS-MCG
SCALE 2":100

COMPANY	SAVIA PERU S.A		
WELL	LOG-26XD		
FIELD	LOBITOS		
PROVINCE/COUNTY	PIURA		
COUNTRY/STATE	PERU		
LOCATION	N: 9 508 662.12m E: 459 045.17m		
Permanent Datum SEA LVL, Elevation 50 feet Log Measured From KB Drilling Measured From KB.	Other Services MDL MDN		MPD CMI
	Elevations: KB DF GL		feet 50.00 50.00 -335.00
Date	05-JAN-2013	07-JAN-2013	
Run Number	ONE	TWO	
Service Order	796	796	
Depth Driller	9800.00	9800.00	feet
Depth Logger	6942.00	9600.00	feet
First Reading	7700.00	7700.00	feet
Last Reading	5850.00	5850.00	feet
Casing Driller	5898.00	5898.00	feet
Casing Logger	5886.75	5886.75	feet
Bit Size	8.500	8.500	inches
Hole Fluid Type	WATER BASED		WATER BASED
Density / Viscosity	1.41 g/cc	19.00 CP	1.41 g/cc
PH / Fluid Loss	9.40	4.80 CC/30Min	9.30
Sample Source	ACTIVE PIT		ACTIVE PIT
Rm @ Measured Temp	1.40 @ 76.0	ohm-m	1.45 @ 78.0
Rmf @ Measured Temp	0.95 @ 78.0	ohm-m	0.95 @ 78.0
Rmc @ Measured Temp	3.0 @ 78.0	ohm-m	2.60 @ 80.0
Source Rmf / Rmc	PRESS	FILTER	PRESS
Rm @ BHT	0.88 @123.0	ohm-m	0.80 @136.0
Time Since Circulation	10:00 05JAN		23:00 08JAN
Max Recorded Temp	123.00	deg F	136.00
Equipment / Base	16064	TAL	16064
Recorded By	YANINA MENDEZ		YANINA MENDEZ
Witnessed By	CESAR MORALES		CESAR MORALES

REMARKS

- Objective: to obtain accurate open hole Gamma Ray , SP, Caliper 8 arms, Resistivity (Dual Laterolog), Sonic log in the 8.5" section.
- This is the First Log done in this well. RULS 206.31ft ;
- All WFT logging depth control applied.
- Casing Shoe was found at 5886.75 ft MD.
- Maximum recorded temperature measured by Gamma Ray sensor: 136°F.
- Mud resistivity measurements: Rm= 1.4 @ 76 °F, Rmf= 0.95 @ 78 °F, Rmc= 3.00 @ 78 °F.
- Mud resistivity measurements at BHT: Rm= 0.799 @ 136°F, Rmf = 0.554@ 136°F, Rmc= 1.75 @ 136°F.
- Well sketch as per driller depth.
- Main section from TD to 8500ft and from 7900ft to 3540 ft MD as per client requirements .
- No Repeat Section due to bridged.
- Hole volume= 1085ft^3
- Annular volume= 750ft^3 for a 5.5" casing.
- Average:
X caliper: 10.706"
Y caliper: 9.396"
X caliper: 9.92"
Y caliper: 9.058"
- The scales and shading of the curves are as per client requirements.
- Enviromental corrections.
- Gamma Ray: Mud density, Caliper.
- Laterolog: Standoff, caliper, mud resistivity.
- Maximun deviation 34.50deg @ 4525 ft and maximun dogleg severity 5.55deg @ 410.00ft
- Neutron and GR logged to 3550ft as per client request.
- Toolstring bridged @ 7164ft. Try to pass the point for two hours. Then with client assurance we proceed to log from there to 3550ft.
- At secpnd attempt the toostring bridged again @ 7715ft. The cliente decided to log this part and removed the sonic at surface (MSS) to decreased the lenght of the toolstring, and move the SKJ to another position, removed the hole finder which was damaged after two bridgeds. The tool was ran again and after several attempts to reach TD, the maximun depth achieved was 7899ft. After these attemots to reach TD the client decided to run TDL.
- The data from the bottom part, obtain by TDL-CWS is on depth with the mule shoe (8500ft).

21. The data obtain with the TDL-CWS will be send to double check to try to get a better data quality

Crew at your service:

Y. Mendez / J. Jimenez / P. Marcelo / G. Chavez / E. Cruz / E. Roldan / J. Guerrero

BOREHOLE RECORD

Last Edited: 05-JAN-2013 14:44

Bit Size inches	Depth From feet	Depth To feet
17.000	0.00	1898.00
12.250	1898.00	5898.00
8.500	5898.00	9800.00

CASING RECORD

Type	Size inches	Depth From feet	Shoe Depth feet	Weight pounds/ft
surf	13.375	0.00	1898.00	54.50
interm	9.625	0.00	5898.00	43.50

WELL DIAGRAM

13.38 in Casing: 0.00 ft

9.63 in Casing: 0.00 ft

17.00 in Bit size: 0.00 - 1898.00 ft

13.38 in Casing shoe: 1898.00 ft


12.25 in Bit size: 1898.00 - 5898.00 ft

9.63 in Casing shoe: 5898.00 ft

8.50 in Bit size: 5898.00 - 9800.00 ft

Total bit depth: 9800.00 ft

Temperature: 123.00 Degrees F



DOWNHOLE EQUIPMENT

I:\LO6_26XD\Final\repro5.dta

CBH-C, Cablehead, 11 pin

CBH-CC 124 LG: 2.40 ft WT: 24.3 lb OD: 2.24 in

SHA-J.A Compact Swivel Head Adaptor

SHA-J.A 229 LG: 2.30 ft WT: 22.0 lb OD: 2.24 in

Compact Stiff Bridle Electrode Sub.

MBE-C.B 260 LG: 12.33 ft WT: 77.2 lb OD: 2.28 in

Compact Stiff Bridle Electrode Sub.

MBE-C.B 261 LG: 12.33 ft WT: 77.2 lb OD: 2.28 in



90.31 ft SPDL - Spontaneous Potential

SKJ-D.A Compact Knuckle Joint
SKJ-D.A 171 LG: 2.17 ft WT: 24.3 lb OD: 2.24 in

Compact Comms Gamma
MCG-D.A 261 LG: 8.70 ft WT: 63.9 lb OD: 2.24 in

MIS-D.B Compact Inline Bowspring sub
MIS-D.B 755 LG: 5.70 ft WT: 33.1 lb OD: 2.24 in

Compact Neutron
MDN-C.A 442 LG: 5.04 ft WT: 50.7 lb OD: 2.24 in

Compact Density/Caliper
MPD-C.A 238 LG: 9.59 ft WT: 90.4 lb OD: 2.24 in

SKJ-E.B Compact Knuckle Joint
SKJ-E.B 507 LG: 2.17 ft WT: 24.3 lb OD: 2.24 in

Compact Upper Guard Sub.
MUG-A 47 LG: 8.98 ft WT: 68.3 lb OD: 2.24 in

MIS-E.B Compact Inline Standoff sub
MIS-E.B 633 LG: 2.14 ft WT: 15.4 lb OD: 2.24 in

Compact Laterolog Electrode Sub.
MLE-D.A 227 LG: 12.34 ft WT: 92.6 lb OD: 2.24 in

MIS-E.A Compact Inline Standoff sub
MIS-E.A 150 LG: 2.14 ft WT: 15.4 lb OD: 2.24 in


Compact Lower Guard Sub.
MLG-B.A 139 LG: 8.00 ft WT: 55.1 lb OD: 2.24 in

SKJ-E.B Compact Knuckle Joint
SKJ-E.B 547 LG: 2.17 ft WT: 24.3 lb OD: 2.24 in


Compact MMI Electrode Section
MIE-A.A 171 LG: 13.96 ft WT: 99.2 lb OD: 2.40 in


Compact Hole Finder
HFS 1 LG: 0.92 ft WT: 2.2 lb OD: 2.24 in



Total Length: 113.35 ft Weight: 859.8 lb






All interpretations are opinions based on inferences from electrical or other measurements and we cannot, and do not, guarantee the accuracy or correctness of any interpretations, and we shall not, except in the case of gross or wilful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions in our price schedule.











Depth Based Data - Maximum Sampling Increment 10.0cm

Filename: I:\LO6_26XD\Final\Final_v1.dta

System Versions: Plotted with 13.04.8723

Plotted on 22-JAN-2013 17:19

Recorded on 05-JAN-2013 20:13

↑ MAIN PASS ↑

COMPANY		SAVIA PERU S.A			
WELL		LO6-26XD			
FIELD		LOBITOS			
PROVINCE/COUNTY		PIURA			
COUNTRY/STATE		PERU			
Elevation Kelly Bushing	50.00	feet	First Reading	7700.00	feet
Elevation Drill Floor	50.00	feet	Depth Driller	9800.00	feet
Elevation Ground Level	-335.00	feet	Depth Logger	6942.00	feet
		SONIC LOG			
Weatherford [®]		MSS-MCG			
		SCALE 2":100			